


MOTORCYCLE BATTERY

HPG20H-3-1 (12V 18Ah)



CHARACTERISTICS


Item	Specifications	
Nominal Voltage	12V	
Nominal Capacity (10HR)	18Ah	
Cold Cranking Performance Amps@0°F (-18°C)	250A	
Dimension (±2mm)	Length	175mm (6.89inches)
	Width	87mm (3.43inches)
	Container Height	155mm (6.10inches)
	Total Height	155mm (6.10inches)
Battery (with acid)	Approx Weight	5.93kg (13.1lbs)
Terminal type	A	
Battery type	HPG Series	
Voltage Full Charge	Constant-Voltage Charge:	
	Initial charging current	Less than 0.3C ₁₀
	14.40V~15.00V at 25°C (77°F)	
	Charging time	15~18h
	Constant-Current Charge:	
	Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge Voltage	Initial charging current	Unlimited
	13.50V~13.80V at 25°C (77°F)	
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%



GENERAL FEATURES

- Longer lifespan
- Lower self-discharge
- Totally Maintenance-free
- Shipped pre-charged and ready to install

Discharge Characteristics (25°C, 77°F)



*Values are subject to variation of +/- 5% in normal manufacturing processes.

ZAFER ENERGY SYSTEMS IND.&FOREIGN TRADE CO.LTD.

Head Office

Beylikdüzü O.S.B Mermerciler San. Sitesi
9. Cadde No:18 Beylikdüzü
İSTANBUL/TURKEY
TEL : +90(212)632 05 35
FAX : +90(212)632 05 87
WEB : <http://www.zaferenergy.com>

