

EO SERIES-AGM Battery



EO12250 (12V250AH)

Specification

Nominal Voltage	12V	
Nominal Capacity(10HR)	250.0AH	
Dimension	Length	522±2mm (20.55 inches)
	Width	268±2mm (10.55 inches)
	Container Height	220±2mm (8.66 inches)
	Total Height (with Terminal)	226±2mm (8.90 inches)
Approx Weight	Approx 77.0 Kg (169.8 lbs)	
Terminal	T11	
Container Material	ABS	
Rated Capacity	267.5 AH/13.38A	(20hr , 1.80V/cell,25°C/77°F)
	250.0 AH/25.0A	(10hr,1.80V/cell,25°C/77°F)
	217.5 AH/43.5A	(5hr,1.75V/cell,25°C/77°F)
	195.0 AH/65.0A	(3hr,1.75V/cell,25°C/77°F)
	155.0 AH/155.0A	(1hr,1.60V/cell,25°C/77°F)
Max. Discharge Current	2500A (5s)	
Internal Resistance	Approx 2.5mΩ	
Operating Temp.Range	Discharge : -15~50°C (5~122°F)	
	Charge : 0~40°C (32~104°F)	
	Storage : -15~40°C (5~104°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 75.0A.Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	EO series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ UPS and EPS
- ◆ Emergency light
- ◆ Railway signal and aircraft signal system
- ◆ Marine and power stations Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply, DC power supply

Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	292.5	246.0	218.3	181.0	139.7	119.5	77.4	58.2	47.7	40.1	35.1	28.2	24.2	12.9
1.80V/cell	334.7	276.2	241.3	196.6	150.7	126.1	83.2	62.5	50.7	42.5	37.2	29.7	25.0	13.4
1.75V/cell	380.1	311.3	266.7	213.6	164.3	137.5	86.5	65.0	52.4	43.5	38.4	30.7	25.7	13.7
1.70V/cell	429.3	345.4	294.3	233.2	177.0	145.5	91.1	68.4	54.8	46.0	40.2	31.9	26.7	14.1
1.65V/cell	461.0	369.8	313.1	246.1	187.3	150.5	94.5	71.2	56.9	47.5	41.6	33.0	27.4	14.5
1.60V/cell	\	405.1	340.2	262.6	194.7	155.0	96.9	73.0	58.2	48.6	42.5	33.6	28.0	14.7

Constant Power Discharge (Watts) at 25 °C (77°F)




F.V/Time	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	546.2	464.0	415.8	348.6	271.3	232.9	151.8	114.6	94.1	79.4	69.8	56.2	48.4	25.9
1.80V/cell	617.7	514.1	453.0	372.9	290.4	244.5	162.1	122.4	99.5	83.8	73.6	59.0	49.9	26.7
1.75V/cell	690.4	572.3	495.9	401.9	313.7	265.3	168.0	126.8	102.6	85.5	75.7	60.8	51.2	27.4
1.70V/cell	762.3	626.2	543.3	436.4	336.7	279.9	176.6	133.2	107.0	90.2	79.2	63.3	53.1	28.0
1.65V/cell	811.2	665.4	573.7	456.8	353.1	287.5	182.0	138.0	110.8	92.8	81.7	65.3	54.5	28.9
1.60V/cell	\	716.9	616.5	484.0	365.0	294.5	185.7	140.9	112.9	94.7	83.2	66.3	55.6	29.3

Specifications subject to change without notice.


Dimensions

T11 Terminal


Unit: mm [inches]




Discharge Characteristics





Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Self Discharge Characteristics

- A** No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
 2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
 3. Charged for 8~10 hours at limited current 0.05CA.
- C** Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

Specifications subject to change without notice.

Sales Office



ZAFER ENERGY SYSTEMS IND.&FOREIGN TRADE CO.LTD.

Head Office

Beylikdüzü O.S.B Mermeciler San. Sitesi
9. Cadde No:18 Beylikdüzü
ISTANBUL/TURKEY
TEL : +90(212)632 0535
FAX : +90(212)632 0587
WEB : <http://www.zaferbattery.com>